

Raysun CVT Fluid

Multi-Vehicle Continuously Variable Transmission (CVT) Fluid

Raysun CVT Fluid is exclusively designed with the well-balanced blend of high-performance additives and carefully selected base fluids to provide suitable performance in a wide-range of CVT equipped passenger vehicles. Its performance has been demonstrated in different areas required for CVT fluid, including low-temperature fluidity, oxidation stability, wear protection, anti shudder durability, shear stability, material compatibility, metal-to-metal friction and foaming prevention. It provides suitable performance in a wide-range of CVT-equipped passenger vehicles and meets or exceeds the requirements of most Japanese, European and North American OEM CVT fluids for service-fill applications

Advantages

- Provides high metal to metal friction performance
- Improved anti-shudder properties ensuring smooth operations
- Shear Stable viscosity modifier ensures long lasting Shear Stability during the operation
- Excellent anti-foam characteristics ensure proper lubrication at all times
- It's backed with extensive test data demonstrating the Suitability For Use in the place of many OEM CVT fluids

Applications

- Recommended for wide range of passenger car CVT fluid service-fill applications

.(Note : Not suitable for use in hybrid CVT units (Ford and Toyota

Specifications

▪ Toyota CVTF TC	▪ Subaru iCVT
▪ Toyota CVTF FE	▪ Subaru Lineartroincs HT Chain CVT
▪ Nissan NS-1, 2, 3	▪ Daihatsu Ammix CVT

Honda HMMF (not for Honda CVT with starting clutch) ■
raysun
 Raysun Oil Co.

Suzuki CVTF ■

Raysun CVT Fluid

Honda HCF2 ■	Suzuki NS-2 ■
Mitsubishi SP-III ■	Suzuki CVT Green 1& 2 ■
Mitsubishi CVTF-J1 ■	Hyundai SP-III (CVT (Model ■
Mazda JWS 3320 ■	Chrysler Jeep NS-2/CVTF +4 ■
Subaru ECVT ■	GM DEX CVT ■
	Mini Cooper EZL 799 ■

Typical Values	ASTM Method	Specification
7	D 445	Viscosity @ 100 °C, cSt.
185	D 2270	Viscosity Index
216	D 92	Flash Point, °C
۰۲۱-۲۲۸۲-۲۳۵ فکس: ۰۲۱-۲۳۵۵۰ تلفن: www.raysunoil.com	دفتر مرکزی: پاسداران، چهارراه فرمانیه، خیابان شهید جهانبخش نژاد (نارنجستان هفتم)، کارخانه: اتوبان تهران قم، شهرک صنعتی شمس آباد پلاک ۱۰، طبقه چهارم	شرکت نفت ری سان Our Point, °C
13000	D 2983	Brookfield Viscosity, @-40 °C, cP

Note: "All of the results are typical and the results of each batch are presented in the COA sheet."

