

Raysun Triton PE

High Performance Synthetic Refrigeration Compressor Lubricant

Raysun Triton PE series are high performance fully synthetic refrigeration compressor oils specially designed to meet the stringent requirements of most modern refrigeration and air conditioning systems that are filled with the new ozone friendly refrigerant R-134a and other environmentally acceptable HFC refrigerants. These oils are formulated with Polyol Ester base fluids and provide excellent protection against oxidation degradation, wear and rust & corrosion. These oils are specifically designed for refrigeration systems using HFC refrigerants such as R-134a, R-23, R-404A, R-407C, R-507 and other blends of HFC refrigerants. These oils exceed the performance requirements of DIN 51503 KD and ISO 6743-3:2003 L-DRD, L-DRE, L-DRF and L-DRG.

Advantages

- Excellent thermo-oxidative stability controls deposits in evaporator tubes, improves heat transfer and improves oil life resulting in improved equipment reliability, availability and efficiency
- Very good solubility, particularly with R-134a, R23 and comparable refrigerants as well as blends of those refrigerants over a wide range of operating temperature. Also compatible with HFC, CFC/ HCFC and HC type refrigeration gases
- Excellent wear and rust protection results in reduced maintenance costs and longer equipment life
- Completely wax free and lower pour point prevents blockage and ensures smooth operation
- Readily biodegradable and can be disposed of through conventional methods
- Compatible with elastomers commonly used in the refrigeration system

Applications

- Mobile air conditioning, domestic refrigeration, residential and commercial air conditioning and heat pump, commercial refrigeration including transport refrigeration, Industrial refrigeration (reciprocating and rotary units) using HFC, CFC/ HCFC, Carbon dioxide, HC refrigerants
- Marine refrigeration applications line food freezing and cold storage plants
- Suitable for use with most hydrofluorocarbon refrigerant gases like R-134a, R-23, R125, R-143a, R-152a, R-404A, R-407A, R-407C, R-408A, R-410A, R-507A and non-hydrofluorocarbon R-12, R-22, R-23, R-32, R-500, R-501, R-502, etc compressors where such quality oils are recommended

NOTE: These oils are not recommended for use with ammonia refrigerants

Raysun Triton PE

ISO Viscosity Grades											ASTM Method	Specification
370	320	220	170	150	100	68	55	46	32	22		
0.968	0.968	0.967	0.966	0.965	0.962	0.959	0.957	0.955	0.950	0.945	D 1298	Density @ 15°C, kg/l
370	320	220	170	150	100	68	55	46	32	22	D 445	Viscosity @ 40 °C, cSt.
88	91	93	95	102	103	125	125	125	135	140	D 2270	Viscosity Index
294	286	284	282	280	278	274	272	270	266	260	D 92	Flash Point, °C
-18	-21	-27	-33	-36	-39	-42	-42	-45	-48	-48	D 97	Pour Point, °C
0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	D 664	Total Acid number, mg KOH/g

Note: "All of the results are typical and the results of each batch are presented in the COA sheet."